



✉ tstevens@gatewayintl360.com
 🌐 www.gatewayintl360.com
 📍 P. O. Box 518, Bear, DE 19701

Gateway International 360, LLC

GATEWAY 360, BORN FOR GREEN ENERGY SOLUTIONS

GW-EV100

Level 2

Up to 48A



READY TO HANDLE THE MOST POWERFUL EV BATTERIES



POWERFUL

1-port with up to 40A and 10.0kW per port of charging capacity.



DURABLE

NEMA 250 and Type 3R protection ratings allow for indoor or outdoor installation.



INTERACTIVE

4 LED indicators - Power, Connect, Charging & Fault



CONNECTED

Complete with LAN connectivity (Wi-Fi or 4G optional), ensuring chargers are always online.



OCPP ENABLED

OCPP 1.6J helps you connect the EV charger to the cloud.



FLEXIBLE

Cable management allows access to either side of the vehicle.



DATA SHEET

Model No.	GW-EV100-116U	GW-EV100-132U	GQ-EV100-140U
Input Voltage	230V	230V	230V
Frequency	60Hz	60Hz	60Hz
Amperage	16A	32A	40A
Max. Power Output	3.5kW	7.0kW	10.0kW
Net Weight	17.67 lbs		
Gross Weight	17.67 lbs		
Package Dimensions	15.70" x 12.66" x 10.50"		
Package Dimensions	12.20" x 8.66" x 3.75"		

Protection & Standard

Charging Interface	SAE J1772 Compliant, Type 1 Plug
Safety Compliance	UL 2231-1, UL2232-2, UL2594, ROHS, CE, REACH, FCC
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection

Environmental

Operating Temp.	-30° to 50°C (-22° to 122°F) ambient
Relative Humidity	Up to 95% non-condensing
Cable Length	5m/16ft or custom length

HOME APP

Manage your charging activity

- Connect via Wifi or Bluetooth
- Remote start or stop charging
- Schedule your charging time
- Dynamic load balance setting
- View charging history and power consumption
- Restart button

