



Gateway International 360, LLC

GATEWAY 360, BORN FOR GREEN ENERGY SOLUTIONS

✉ tstevens@gatewayintl360.com
🌐 www.gatewayintl360.com
📍 P. O. Box 518, Bear, DE 19701

GW-EV4000

DCFC

60/90/120/150/180kW

2^y ears
mited
warranty



POWERFUL

Up to 150kW of charging capacity.



COMPATIBLE

CCS Type 1 plug with 18ft cable.



RELIABLE

Optimal functionality in a wide range of conditions.



FLEXIBLE

Fast and easy set-up and installation anywhere.



MODULAR

For easy and low-cost maintenance service.



SMART

OCPP 1.6J help you connect EV charger to the cloud.



DATA SHEET

Model No.		GW-EV4000-2-60	GW-EV-4000-2-90	GW-EV-4000-120	GW-EV-4000-2-150	GW-EV-4000-2-180
AC Input	Number of phase / wire	3ph / L1,L2, L3, N, PE				
	Voltage Rating	480Vac（+10%, -15%）				
	Max. InputAmperage	100A	135A	180A	226A	270A
	Frequency	60Hz				
	Power factor	PF≥0.98@Rated load				
DC Output	Efficiency	>91%				
	Maximum Power	60KW	90KW	120KW	150KW	180KW
	Voltage Operating Range	200-1000V				
	Maximum Current	60A@1000Vdc	90A@1000Vdc	120A@1000Vdc	150A@1000Vdc	180A@1000Vdc
	Connector and Cable	CCS1 with 13ftcable				

EV Communication	ISO 15118
User Authentication	ISO 14443 A/B
Display	7 inch touch screen
Network	Ethernet, LTE, Wi-Fi
Connectivity	OCPP 1.6J

Protection & Standard

Certificate	ETL, FCC
Safety Compliance	UL2202, UL2231-1 and UL2231-2
Multiple Protection	OVP, UVP, OPP, OTP, SPD, RCD, IMD, OCP
Warranty	5 years

Environmental

Storage Temperature	-40°F to 158°F
Operating Temperature	-22°F to 122°F
Anti-vandalism	IK10(not includeLCD & RFID cover)
Ingression	NEMA 3R
Relative Humidity	Up to 95% non-condensing
Cooling	Forced Air
Operating noiselevel	≤65dB
Altitude	≤6561ft

