

EV75 SERIES

Level 2 EV charging station, 1-port, up to 60A input and selectable charging output from 5.6kW to 11.5kW.



SPECIFICATIONS

Input Current	48/40/32A
Input Voltage (Single phase)	200-240V / 60Hz
Network Connectivity	Built-in WiFi (802.11 b/g/n/2.4GHz) / Bluetooth
OTA Technology	Included
Plug	SAE J1772 Type 1
Number of Ports	Single
Charging Cable	18 ft
OCPP 1.6	Yes
Open ADR 2.0b Compliant	N/A
CTEP	Yes
AC Input Connection	L/N/GND
Max Output, 60 Hz	48A / 11.5kW
Hardwired	Yes
Dimensions (H x W x D)	12.3 x 10.2 x 4.1 inches
Weight (Lbs)	8.8 Lbs
IP Protection	NEMA Type 4
Tamper Resistant	IK10
Cable Management	Optional
Operating Temperature	-22 to 122 °F
Humidity	Max 85%
Metering Accuracy	+/- 1%
Input Protection	UVP, OVP, RCD, SPD
Output Protection	OCP, Control Pilot Fault
Internal Protection	OTP, MCU function fault
Safety	UL2594, NEC 265
FCC compliant	Yes
Energy Star Certified	Yes
Power Configurable	Built-in (11.5, 7.4, 5.6kW output)



Made in America option coming soon. Contact factory for details.

Download the app onto your phone or tablet from the Apple App Store or Google Play.

Create account and begin the setup process.



ORDERING INFORMATION

MODELS	
GW-EV75	EV charger, Level 2, 1 port, 48A/11.5kW
ACCESSORIES (ordered separately)	
GW-EVHOOK	Cable hook for Level 2 EV charger
PEDESTALS (ordered separately)	
GW-EVP-S	Pedestal for single Level 2 AC EV charger
GW-EVP-D	Pedestal for dual Level 2 AC EV chargers
GW-EVP-S-CM	Pedestal with cable management for single Level 2 AC charger
GW-EVP-D-CM	Pedestal with cable management for dual Level 2 AC chargers